# BB DCTTX

### **BOILER FILLING COCKS**









#### PRODUCT CATALOGUE

#### **Boiler filling cocks**



Boiler filling cock recessed brass cap



Boiler filling cock
black lever



**Boiler filling cock** red lever self-closing



**Boiler filling cock** self-closing red lever, brass nickel plated



#### INTRODUCTION

BONFIX B.V. supplies a large range of BONFIX brass boiler filling cocks in brass and brass nickel plated models.

#### **TECHNICAL INFORMATION**

The technical specifications are based on the current industry and regulatory status. BONFIX B.V. reserves the right to modify technical specifications without prior notice. No rights can be derived from the technical information provided in this brochure.



#### **GENERAL**

BONFIX boiler filling cocks are designed for the filling and draining of radiators and central heating installations.

#### **PRODUCT USAGE**

BONFIX boiler filling cocks can be used in central heating systems, water supply and irrigation systems. Other forms of usage, depending on pressure/ temperature and medium, may be admissible but require prior written approval by **BONFIX B.V** 

#### **TECHNICAL SPECIFICATIONS**

BONFIX boiler filling cocks are manufactured from premium quality brass (CuZn4OPb2) and provided with a ball valve with and open and closed position, a long exterior tapered thread, and a heavy duty hose fitting. BONFIX boiler filling cocks can be used in systems with an operating pressure not exceeding 1000 kPa (10 bar) and a temperature not exceeding +90 °C.

#### **QUALITY MARK**

BONFIX boiler filling cocks do not bear a quality mark.

#### **INSTALLATION INSTRUCTIONS**

For sealing the connection, we recommend the use of an approved GASTEC tape on the long exterior thread. When opening or closing the fill/drain valve, cap or lever, never rotate more than ¼ turn.

Other forms of usage, depending on pressure/temperature and medium, may be admissible but require prior written endorsement by BONFIX B.V.



riangle Use appropriate tools for installation and prevent damage.

#### **WARRANTY AND LIABILITY**

Warranty and liability apply as per our general terms and conditions. Damage caused by stress corrosion is not covered under product warranty.



# BB bonfix Superieur

## SUPERIOR IN PRICE & QUALITY





#### LIKE BONFIX ON FACEBOOK

- ✓ Always up to date on new products
- ✓ Fun actions and specials
- ✓ Direct contact with BONFIX staff OR
- ✓ Visit our website: www.bonfix.eu